



蘉

Reproduction of this document in any form by other than activities of the Department of Defense is not authorized unless specifically approved by the Secretary of the Navy or the Chief of Naval Operations as appropriate.

E

E

25

X

Ē

ľ.,

L

in .

Ł

¥.

L

ľ

F

i

PHYSICAL, CHEMICAL, AND RADIOLOGICAL PROPERTIES OF SLURRY PARTICULATE FALLOUT COLLECTED DURING OPERATION REDWING

Research and Development Technical Report USNRDL-TR-170 NS 088-001

5 May 1957

by

N.H. Farlow W.R. Schell

Chemistry General

Technical Objective SR-2

- 1

Radiological Capabilities Branch T. Triffet, Head

Chemical Technology Division E.R. Tompkins, Head

Scientific Director P.C. Tompkins

L E

X

Ľ

10

Commanding Officer and Director Captain Floyd B. Schultz, USN

U.S. NAVAL RADIOLOGICAL DEFENSE LABORATORY San Francisco 24, California

-

LLL

UNCLASSIFIED

£

1. . X.

1

ġ.

E

28

X

Ł

L

E.

1

ABSTRACT

The properties of individual fallout particles produced by nuclear detonations at zero height over shallow sea water are analytically described for the first time. The particles produced during Operation REDWING were slurry masses composed of water, dissolved and crystalline sea salts, and seawater-insoluble solids from the weapon, barge, and ocean floor. Special techniques were used to measure the chloride, water, and insoluble-solids content of individual slurry particles. Autoradiography showed that the activity is primarily associated with the solids.

A table of experimental data presents particle size versus time of arrival after detonation as well as measurements of particle density and relative specific activity. Estimates of mass and relative activity of fallout per unit area for certain locations about the shot point are shown.

ii

SUMMARY

The Problem

Nuclear devices fired over sea water at previous weapons tests yielded fallout which was different from that associated with land surface detonations. The analytical methods previously used on dry fallout were grossly inadequate for this slurry-like material.

Certain tests at Operation REDWING yielded slurry-like fallout. Therefore, new analytical methods were required to assess the material properly.

Findings

1

K

1

L

The fallout from two seawater-surface nuclear events at Operation REDWING has been analyzed using new quantitative techniques for the measurement of chloride and slurry droplet water content. Particle size, density and radiological properties of the slurry fallout have been assessed satisfactorily for the first time.

Å.

Į.

UNCLASSIFIED

Š.

£.,

Г

2

E

ADMINISTRATIVE INFORMATION

The experimental study reported was initiated to develop methods for the analysis of samples obtained from Project 2.6.3, Operation REDWING. The study was done under Bureau of Ships Project Number NS 088-001, Technical Objective SR-2, and is described as Program 2, Problem 1, in this laboratory's "Preliminary Presentation of USNRDL Technical Program for FY 1957, "February 1956.

L

UNCLASSIFIED

E

÷.

¥.,

.

2

ž.

Ľ

20

R

I I

L

ACKNOWLEDGMENTS

Appreciation is expressed to Mr. W. Williamson, Dr. L. Werner and Mr. B. Chow of this laboratory, Mr. S. Rainey and CDR T.E. Shea of the Bureau of Ships, Washington, D.C., and Mr. S. Majeski of the New York Naval Shipyard, Brooklyn, for their assistance in certain field phases of this project. The contribution by Mr. J.Quan and Mr. J. O'Connor of this laboratory's Analytical and Standards Branch is noteworthy. The assistance by Mr. D. Puppione and Mr. V. DaGragnano, also of this laboratory, in data analysis is appreciated. The editorial advice given by Mr. J. Todd has been invaluable in the preparation of this report.

v

×.

y 4-

UNCLASSIFIED

1

Å.,

E

INTRODUCTION

Some of the nuclear devices fired in Operation REDWING during the Spring of 1956 at the Eniwetok Proving Ground were detonated on or near the surface of the lagoon water. Up to this time, only limited data had been gathered on the physical-chemical-radiological properties of individual fallout particles from such bursts. Therefore, two events, Flathead and Navajo, were selected as subjects for an extensive fallout study.

The nuclear devices fired were situated on steel barges anchored in relatively deep lagoon water. The principal sources of material expected to comprise the fallout were the barge complex, the surrounding seawater and perhaps some lagoon bottom solids. It was hypothesized that sea salts would constitute the major portion of any fallout. With this in mind, a special reagent film¹, quantitative for submicroscopic amounts of chloride, was developed. Since sea salts are hygroscopic, it was felt that the fallout particles would pick up atmospheric water and arrive at the sampling stations as slurry-like droplets. Therefore, the reagent film was calibrated to measure this water content.² The influence of the barge complex on particle composition was unassessed prior to the Operation.

Sampling stations were located at varying distances from the shot points. These stations were aboard anchored barges, type YFNB, and manned ships, type YAG and LST. An array of specialized sampling devices was located at each station. Particles collected in the incremental type of collector, ^{3,4} were used for these fallout studies. Since this device sequentially exposed trays containing chloride reagent film, particles could be classified by time of arrival. One of the ship sampling stations was connected by an elevator device to a radiation-shielded laboratory, permitting almost immediate examination of fallout samples.

METHODS OF ANALYSIS

Ľ

R

The analytical methods developed were so devised that the physical, chemical, and radiological properties of the individual particles could

UNCLASSIFIED

E

be evaluated. Physical observation could detail the state of the material as it landed at the station. Chemical treatment would allow the separation and measurement of soluble salts and seawater-insoluble ones which were to be defined as "insoluble solids." Radiological evaluation would assess the particle radioactivity. These experimental values then would define the physical state of the particles, particle size, density, particle specific activity, total activity, and mass of fallout per unit area.

Assessment of Physical Properties

Visual observations made in the shielded laboratory confirmed the slurry droplet nature of the fallout. Crystalline materials were observed to be suspended in the liquid portion of the droplets. The characteristic cubic shape of sodium chloride was detected. After the dissolution of soluble halides, an insoluble-solids component remained on the film. It was apparent that the slurry droplets contained three major constituents: water, soluble sea salts, and insoluble solids from the environmental materials (Fig. 1).

Measurement of Halide Content

The reagent film for particle halide analysis utilized a commercial gelatin film in which colloidal red silver dichromate was precipitated by a special method.¹ Soluble halides deposited on the film were later dissolved by saturated hot water vapor and diffused into the gel structure where they were precipitated as silver salts. A microscope measurement of the reaction area yielded, by calibration, the weight of halides reported as sodium chloride. The measurable range of sodium chloride by this method is from 10^{-6} to 10^{-12} g.

Measurement of Water Content

Γ

2

When a droplet strikes the reagent film it spreads to a certain constant degree related to the volume of water in the droplet, ⁵ Insoluble solids within each fallout slurry droplet outlined this maximum spread on the collecting film. A calibration curve² was constructed giving the volume of water in a slurry droplet as a function of the area covered by the insoluble-solids trace. This area has been termed the "slurry artifact." The smallest water volume measurable by this technique is about 10^{-10} cc.

Ľ

UNCLASSIFIED

Γ

2



Fig. 1 Reaction of Slurry Fallout Particle on Reagent Film. The white circular area is halide reaction representing 2.9×10^{-7} g NaCl. The central elliptical area is slurry artifact of insoluble solids representing 7.2×10^{-7} cc. Particle density is 1.19 g/cc. The annular rings in the chloride reaction area are thought to be a Liesegang phenomenon.

-3-

E.

I.

A

UNCLASSIFIED

£

ż

Measurement of Insoluble-Solids Content

No known chemical method can measure the weight or volume of insoluble solids in a deposited slurry fallout particle. Therefore, a method for comparing the volume of the fallout particle with standard volumes was developed. Five standard volumes ranging from 10^{-7} to 10^{-9} cc were used for the visual comparison in the microscope. They were formed by aspirating and collecting on reagent film small slurry droplets from measured aluminum oxide suspensions. The water content of each droplet was measured by its slurry artifact. By arithmetic proportion the approximate volume of aluminum oxide was known. Five appropriately sized aluminum oxide artifacts were mounted on a microscope slide as a comparison standard. Each fallout slurry artifact was then visually compared with the standards, and estimates made of the volume of insoluble solids.

The physical-chemical composition of the fallout insoluble solids component is being investigated at this laboratory.

Measurement of Radiological Properties

After solution and diffusion of the soluble halides into the reagent film, autoradiographs were made by adaptations of the LaRiviere-Ichiki method.⁶ These studies showed the activity to be primarily centered in the insoluble-solids portion of the fallout particle (Fig. 2).

These solids were subjected to salt water leaching by the liquid phase of the droplet for at least part of their falling period. Ionic activity available for solution dissolved in this solvent. Upon striking the film the dissolved activity diffused with the water into the gelatin and there was rigidly held. It was felt that if the active solids portion of fallout could be stripped from the film and both parts counted, a rough estimate of easily soluble ionic activity could be made.

One Flathead film sample containing myriads of fallout impressions was selected for stripping and counting. The insoluble solids on the reagent film were thoroughly leached in hot water vapor at 70°C for several hours allowing further diffusion of ionic activity into the film. While the gelatin of the reagent film was still tacky from the vapor treatment, a thick layer of transparent acrylic spray was applied and allowed to dry. The assemblage was then soaked in distilled water for an hour to permit diffusing moisture to loosen the solids from the gel. The acrylic film was then stripped from the gelatin, removing most of the insoluble solids with it. This stripping process was repeated until no microscopically visible insoluble solids remained on the reagent film. The commercial gelatin of the film is so tightly bound to its substrate

-5-

UNCLASSIFIED

that none is removed with the stripped solids. Confirmation of this was obtained by dissolving the acrylic film strippings in organic solvents and examining the solutions for insoluble gelatin pieces; none were observed. Both the stripped reagent film and the removed solids were counted in a crystal well counter.

Sixteen percent of the activity remained on the reagent film. This represents short-exposure, water-soluble activity together with certain colloidal size solids below the visible range of the microscope.

Each of the many other fallout particles with its chloride reaction area was cut from the reagent film. The photon activity was then assessed in the crystal well counter containing a 2-in. NaI(Tl) crystal with a sample well 3/4 in. in diameter and 1-1/2 in. deep. The counting efficiency for fission products is in the region of 40 percent. Decay and coincidence loss curves were constructed for the instrument using early time fallout, enabling activities of individual particles to be reliably corrected to H + 12.

EXPERIMENTAL RESULTS

The condensed and averaged data of Flathead and Navajo are presented in Table 1. The data are grouped in increments of time of arrival at the various ship stations. Some of the particles measured for one variable were not measured for others. Thus a maximum and minimum number of particles measured is sometimes reported for a given time interval.

It was found in general that the insoluble solids comprise less than 4 percent of the weight and less than 2 percent of the volume of slurry droplets. Therefore, in the size and density considerations this component was neglected. It was assumed that the water present in the slurry particles was saturated with sodium chloride. The fact that dissolved sodium chloride occupies about 19 percent less volume in a saturated water solution than does an equal weight of dry crystalline sodium chloride was considered in the calculations.

The activity is primarily associated with the insoluble solids. Since no precise measure of mass or volume of this component is available, activity as a function of sodium chloride mass is reported.

Estimates were made of the specific activity of the insoluble solids. One method involved the direct stripping, weighing, and measuring of activity of solids from a reagent film. Another method involved the

E

-6-

T

UNCLASSIFIED

E

ł



Fig. 2 Autoradiograph of Slurry Fallout Particle Trace and Its Chloride Reaction Area Showing the Radioactivity to be Concentrated in the Centrally Located Insoluble Solids Portion. The black central smear is the autoradiograph masking the solids. Patterns on the reagent film are caused by severe tropical sun reaction on the photosensitive film. Circular spots are NaCl reactions from naturally occurring airborne sea salt particles.

-7-

E

20

E

1

Ē.

-

Time Arriv Inter (H+h	of al val r)	Ship station	No. of Particles Measured	Average NaCl Mass (µg)	Average H ₂ O Mass 2(µg)	Average Density ±Std.Dev. (g/cc)	Average Diameter(a) ±Std.Dev. (µ)	Average Specific Activity ±Std.Dev. (x10 ¹⁰ c/m/g)(b)
****				Flat	head			
l to	3	YFNB-29	4 to 10	0.06	0.08	1.28±0.1	57±6	43±8
7 to	9	YAG-39 8	² 50to52	0.42	0.62	1.29±0.01	112±2	282 ± 20
ll to	12	YAG 40	10	0.94	1.20	1.35±0.05	129±16	285±160
15 to	18	YAG-40	3to4	0.50	0.69	1.34±0.08	121±6	265±90
Total	8		67 to 76			1.30±0.01		282±30
				Nava	ho			
l to	3	YFNB-13	5 to 20	7.77	7.94	1.38±0.04	272±14	4±0.6
3 to	5	YAG-39	9to14	7.62	4.49	1.50±0.1	229±24	16±3
5 to	6	LST-611	14	1.61	1.83	1.41±0.04	166±6	14±2
7 to	9	YAG-40	4tol 0	1.25	1.08	1.45±0.04	142±22	9±3
9 to	10	YAG-40	5to23	0.44	0.60	1.31±0.02	110±5	11±2
10 to	11	YAG-40	llto15	0.66	0,50	1.43±0.03	111±4	16±4
ll to	12	YAG-40	33	0.30	0.44	1.32±0.01	.94±4	$\frac{1}{26}(\frac{1}{6})$
12 to	13	YAG-40	28	0.31	0.31	1.37±0.01	96±2	21(0)
13 to	14	YAG-40	6	0.17	0.27	1.28±0.02	86±7	29(c)
14 to	15	YAG-40	5	0.10	0.18	1.30±0.03	75±2	23(c)
15 to	18	YAG-40	13to14	0.06	0.32	1.15±0.02	84±4	56±7
Total	5	נ	133 to 18 2			1.35±0.01		21±3

Table 1 Slurry Fallout Particle Data

(a) The diameter of the spherical slurry droplet at the time of arrival

(b) Photon count in crystal well counter at H+12

E

(c) Calculated value based on total tray count, number of particles per tray, and average NaCl mass per particle

<u>UNCLASSIFIED</u>

1

E L L X 2 Ł <u>I</u>__ 1_ Ă. í. £. ÷. 2 Å. تبغر

calculation of an average activity per slurry particle, and an estimate of the average volume and weight of insoluble solids per particle by the standard spot comparison method.

The two independent methods gave an average value for Flathead of $1 \times 10^{13} \text{ c/m/g}$ at H + 12 in the well counter. The latter method only was used for Navajo, resulting in a value of $1 \times 10^{12} \text{ c/m/g}$ of insoluble solids.

Table 2 presents experimental data on the total activity per unit area for the two events for various stations. These data are in terms of a count (at H + 12) in the crystal well counter. The total mass of sodium chloride per unit area is a calculated value obtained by dividing the total activity per unit area for a given station (Table 2) by the average activity per NaCl mass (Table 1). Sodium chloride represents the major solid mass of fallout. Since the water content depends on the humidity conditions through which the particle passed, the weight of water is not considered a part of fallout mass. However, if one wishes to compute the approximate weight of water, one multiplies the mass of NaCl by 1.2, which is the average weight ratio of water to NaCl. A plot of the dependent variables, activity per unit area versus NaCl mass per unit area, presents Table 2 data as a necessarily smooth curve (Fig. 3). With this plot one can roughly deduce relative activity by a measure of sodium chloride per square foot or the converse. The very high initial values of sodium chloride mass per square foot have not been plotted on the curve.

DISCUSSION

18

<u>乳 転</u>

L

1. L

Į.

9.--2**64**....

22

25

25

The particle densities (Table 1) cluster about a mean value which is nearly the same for both events. The mean density for the 1- to 3-hr period is close to the overall mean value. By whatever means the ratio of water to solids reaches equilibrium, this mechanism is fairly rapid. Equilibrium has been reached by the time the particle lands.

In Navajo there appears to be a sharp decrease in density after H+13. This time corresponds to the after-sunset hours when changes in ambient atmospheric conditions might be expected.

The particle size (Table 1, "Navajo") generally decreases with time, although it is noteworthy that there is little droplet size variation in 15 hr. For any given time period, one need not discuss particle size distribution since the standard deviation of the mean diameter is so small.

-10-

X.

1

UNCLASSIFIED

¥.

à.

4

. À.

	F1	athead	Navajo				
Collecting Station	Total Activity(a) <u>c/m</u> ft ²	Total Mass NaCl µg/ft ²	Total Activity(a) $rac{c/m}{ft^2}$	Total Mass NaCl µg/ft ²			
YFNB-13-E-57	. ••		143,000,000	3,580			
YFNB-29-H-78	98,400,000	229	6,500,000	31			
YAG 39-C-20	14,800,000	5.25	37,400,000	178			
YAG 39-C-24	3,020,000	1.07	•-				
LST 611-D-37	37,700,000	13.4					
LST 611-D-50	4,850,000	1.72					
YAG 40-A-1	28,800,000	10.2	28,200,000	134			
YAG 40-A-2	31,500,000	11.2					
YAG 40-B-7	11,900,000	4.22					

TABLE 2

Total Activity and Mass of Fallout

(a) Photon count in crystal well counter at H+12.

I I

×

2

Γ

X

-11-

UNCLASSIFIED

1

с~ у 2**м**: Ë.

2

Ε.

<u>.</u>

í E E

2

<u>R</u>

E

<u>ALLI</u>





-12-

Ĩ.

. .

UNCLASSIFIED

3

ور بر منطق ŗ.

£.

.

Early arriving particles appear to have a much higher ratio of sodium chloride to activity than do later arrivals (Table 1, last column.) Such a variation might be indicative of early large droplet fallout from the cloud stem region where the concentration of activity may be less. The sampling is small, however, so caution must be exercised in the interpretation of these data. The calculations of total mean values of specific activity (Table 1) do not include these initial values, nor does the calculation of this value for Navajo include the approximate values defined by footnote (c) of the table.

A comparison of event Flathead with Navajo shows the ratio of total yields is 1:12 while the activities produced by the devices are approximately equal. Since the barge complex for each event was identical, the insoluble solids contributed by this complex are identical for both events. On the basis of activity per gram of sodium chloride, 13 times the amount of seawater was carried aloft by Navajo. Estimates of insoluble solids specific activity indicate that Navajo fallout contained about ten times more solids per activity than did Flathead. Whether this was contributed by calcium and magnesium salts from the seawater carried up by Navajo or by additional bottom material is conjectural.

It appears that the hygroscopic slurry particles can change markedly in size, density, and falling rate due to environmental influences. A detailed study of these effects is required before particle point of origin estimates can be made using measured size data.

Validity of the Data

The data of Table 1 are based on analyses which have been extensively calibrated and tested in the laboratory. The average error in the chloride analysis is about + 5 percent. The standard deviation error of a water volume measurement is about + 25 percent. Estimates of insoluble solids volumes are only approximate and can be subject to large errors. The number of particles sampled for each event is small, but the analyses carried out on each of these is detailed and within the errors shown. Standard deviations quoted in Table 1 are deviations of the mean value, not deviations of a single measurement from the mean.⁷ The radioactivity assay was done with counting instruments thoroughly calibrated and tested. Both standard isotopes and fission-product activities from the actual events were used to evaluate the instruments.

The tabulation of activity per square foot (Table 2) reveals sampling biases which call for caution in the use of these data. Identical adjacent collectors, YAG 39-C-20 and YAG 39-C-24, sampled the same fallout event, yet the total activities recorded for Flathead for these stations differ by a factor of 5. Samplers of somewhat different design considerably

-13-

apart on the same ship, YAG 40-A (2 samplers) and YAG 40-B-7, collected samples differing by a factor of 3. The evaluation of these collection biases is under study at this laboratory.

Obviously, measures of total activity per unit area and perhaps of particle size are influenced by instrument and location biases. However, analyses for particle chloride content, water content, solids volume and activity values are of reasonable precision. These are parameters of individual particles and are not influenced by instrument biases.

Applications

X

8

E

2

I

The analytical techniques used here are directly applicable to a study of atmospheric sea salts. The similarity between the environmental interactions of naturally occurring particles and of slurry fallout is very striking. A study of the former would yield useful information on environmental reactions of slurry fallout.

Approved by:

E. R. Jonpkins

E.R. TOMPKINS Head, Chemical Technology Division

For the Scientific Director

300-3101

Z

LLL

UNCLASSIFIED

£

REFERENCES

- 1. Farlow, N.H. Quantitative Analysis of Chloride Ion in 10⁻⁶ to 10⁻¹² Gram Particles. <u>Anal. Chem. 29</u>: 883, 1957.
- Farlow, N.H. A Method of Measuring Water Content of Airborne Sea Salt Particles. U.S. Naval Radiological Defense Laboratory Technical Report, USNRDL-TR=168, 13 May 1957.
- Triffet, T., LaRiviere, P.D., Evans, E.C., III, Perkins, W.W., and Baum, S. Characterization of Fallout. Operation REDWING, Project 2.63, Interim Test Report ITR-1317, Vol. I, April 1957 (Classified)
- 4. Wittman, J.P., and Goodale, T.C. An Automatic Water Drop Collector for Field Use. Bull. Amer. Meteor. Soc. Vol. 36, No. 2, p. 69, 1955.
- 5. Farlow, N.H. An Improved Halide Ion-Sensitive Sampling Surface for Water Aerosols. <u>Rev. Sci. Instr.</u> 25: 1109, 1954.
- LaRiviere, P.D., and Ichiki, S.K. Autoradiographic Method for Identifying Beta-Active Particles in a Heterogeneous Mixture. Nucleonics 110, 1952.
- 7. Scarborough, J.B. <u>Numerical Mathematical Analysis</u>. The Johns Hopkins Press, Baltimore, 1930, pp 318-328.

-15-

and	Ľ	×.	X	<u> </u>	K		L	1	Γ	-	4	Z		1	E		÷.	1	ž.,	
---	---	----	---	----------	---	--	---	---	---	---	---	---	--	---	---	--	----	---	-----	--

DISTRIBUTION

COPIES

NAVY

1-9	Chief, Bureau of Ships (Code 233)
10	Chief, Bureau of Medicine and Surgery
11	Chief, Bureau of Aeronautics (Code AE40)
12	Chief, Bureau of Supplies and Accounts (Code SS)
13-14	Chief, Bureau of Yards and Docks (D-440)
15	Chief of Naval Operations (Op-36)
16	Commander, New York Naval Shipyard (Material Lab.)
17-19	Director, Naval Research Laboratory (Code 2021)
20-24	CO, Office of Naval Research, New York
25	Office of Naval Research (Code 422)
26	Naval Medical Research Institute
27	CO, Naval Unit, Army Chemical Center
28	CO, Naval Unit, CmlC Training Command
29	CO, U.S. Naval Civil Engineering (Res. and Eval. Lab.)
30	U.S. Naval School (CEC Officers)
31	Commander, Naval Air Material Center, Philadelphia
32	CO, Naval Schools Command, Treasure Island
33	CO, Naval Damage Control Training Center, Philadelphia
34	U.S. Naval Postgraduate School, Monterey
35	CO, Fleet Training Center, Norfolk
36-37	CO, Fleet Training Center, San Diego
38	Office of Patent Counsel, Mare Island
39	Commander Air Force, Atlantic Fleet (Code 16F)
40	Commandant, U.S. Marine Corps
41	Commandant, Marine Corps Schools, Quantico (Library)
42	Commandant, Marine Corps Schools, Quantico (Dev. Center)

ARMY

43-44	Chief of Research and Development (Atomic Division)
45	Deputy Chief of Staff for Military Operations

-17-

UNCLASSIFIED

- 46-47 Assistant Chief of Staff, G-2 48 Chief of Engineers (ENGEB, Dhein) 49 Chief of Engineers (ENGNB) 50 Chief of Transportation (TC Technical Committee) 51 Chief of Ordnance (ORDTN-RE) 52 Chief Chemical Officer 53 CG, Chemical Corps Res. and Dev. Command 54 Hq., Chemical Corps Materiel Command 55 **Ballistic Research Laboratories** 56 President, Chemical Corps Board 57 CO, Chemical Corps Training Command (Library) 58 CO, Chemical Corps Field Requirements Agency 59-60 CO, Chemical Warfare Laboratories 61-62 CG, Aberdeen Proving Ground (Library) 63 Office of Chief Signal Officer (SIGRD-8B) 64 Director, Walter Reed Army Medical Center 65 CG, Continental Army Command, Fort Monroe (ATDEV-1) 66 CG, Quartermaster Res. and Dev. Command 67 Director, Operations Research Office (Librarian) 68 CO, Dugway Proving Ground 69 Office of Surgeon General (AFCSG-15) 70 CG, Engineer Res. and Dev. Laboratory (Library) 71 CO, Transportation Res. and Dev. Command, Fort Eustis 72 Commandant, Army Aviation School, Fort Rucker 73 President, Board No. 6, CONARC, Fort Rucker 74 NLO, CONARC, Fort Monroe 75 Director, Office of Special Weapons Dev., Fort Bliss 76 CO, Ordnance Materials Research Office, Watertown 77 CO, Watertown Arsenal CO. Frankford Arsenal 78 79 Signal Corps Center, Fort Monmouth 80 Tokyo Army Hospital AIR FORCE
 - موک دنده میسه کند به اختیاب می مکند. بعد
- 81 Directorate of Intelligence (AFOIN-3B)
- 82 Commander, Air Materiel Command (MCMTM)
- 83 Commander, Wright Air Development Center (WCRTY)
- 84 Commander, Wright Air Development Center (WCRTH-1)
- 85 Commander, Air Res. and Dev. Command (RDTDA)
- 86 Directorate of Installations (AFOIE-ES)
- 87 Director, USAF Project RAND (WEAPD)
- 88 Commandant, School of Aviation Medicine, Randolph AFB
- 89 CG, Strategic Air Command (Operations Analysis Office)
- 90 Commander, Special Weapons Center, Kirtland AFB
- 91 Director, Air University Library, Maxwell AFB

-18-

.

E

26

E

92-93	Commander, Technical Training Wing, 3415th TTG
94	CG, Cambridge Research Center (CRHTM)
95	CO, Hq., 2D Weather Group, Langley AFB

OTHER DOD ACTIVITIES

96	Chief, Armed Forces Special Weapons Project
97	AFSWP, SWTG, Sandia Base (Library)
98-100	AFSWP, Hq., Field Command, Sandia Base
101	Assistant Secretary of Defense (Res. and Dev.)
102-103	Assistant Secretary of Defense (Civil Defense Div.
104-108	Armed Services Technical Information Agency

AEC ACTIVITIES AND OTHERS

109	Alco Products, Inc.
110-119	Argonne National Laboratory
120	Atomic Bomb Casualty Commission
121-123	Atomic Energy Commission, Washington
124-125	Atomics International
126	Babcock and Wilcox Company
127-128	Battelle Memorial Institute
129-130	Bettis Plant
131-134	Brookhaven National Laboratory
135	Brush Beryllium Company
136	Chicago Patent Group
137	Columbia University (Hassialis)
138	Combustion Engineering, Inc.
139-140	Consolidated Vultee Aircraft Corporation
141	Convair-General Dynamics Corporation
142	Defense Research Member
143	Department of Food Technology, MIT
144	Division of Raw Materials, Casper
145-146	Division of Raw Materials, Denver
147	Dow Chemical Company, Pittsburg
148	Dow Chemical Company, Rocky Flats
149-151	duPont Company, Aiken
152	duPont Company, Wilmington
153-154	General Electric Company (ANPP)
155-160	General Electric Company, Richland
161-162	Goodyear Atomic Corporation
163	Hawaii Marine Laboratory
164-165	Iowa State College
166-167	Knolls Atomic Power Laboratory
1/0 1/0	

168-169 Lockheed Aircraft Corporation, Marietta 170-171

Los Alamos Scientific Laboratory

-19-

<u>UNCLASSIFIED</u>

<u>يمد</u>

 \mathbf{x}

-

2

)

- Mallinckrodt Chemical Works 172-173 Massachusetts Institute of Technology (Hardy) 174 175 Mound Laboratory 176 National Advisory Committee for Aeronautics 177 National Bureau of Standards (Taylor) 178 National Bureau of Standards (Library) 179 National Lead Company, Inc., Winchester 180 National Lead Company of Ohio 181 New Brunswick Laboratory 182-183 **New York Operations Office** Nuclear Development Corporation of America 184 185 Nuclear Metals, Inc. Oak Ridge Institute of Nuclear Studies 186 187-191 Oak Ridge National Laboratory 192 Patent Branch, Washington 193-196 Phillips Petroleum Company 197-198 Public Health Service, Washington 199 **RAND** Corporation 200 Sandia Corporation 201 Sylvania Electric Products, Inc. 202 **Technical Research Group** The Martin Company 203 204 Union Carbide Nuclear Company (C-31 Plant) 205-207 Union Carbide Nuclear Company (ORGDP) 208-211 **United Aricraft Corporation** 212 U.S. Geological Survey, Denver 213 U.S. Geological Survey, Menlo Park 214 U.S. Geological Survey, Naval Gun Factory 215 U.S. Geological Survey, Denver 216 U.S. Patent Office 217 UCLA Medical Research Laboratory 218-219 University of California Radiation Laboratory, Berkeley 220-221 University of California Radiation Laboratory, Livermore 222 University of Rochester (Technical Report Unit) 223 University of Utah (Stover) 224 Vitro Engineering Division 225 Weil, Dr. George L. 226 Westinghouse Electric Corporation 227-252 Technical Information Service, Oak Ridge USNRDL
- 253-280 USNRDL, Technical Information Division

DATE ISSUED: 19 October 1957

-20-

<u>UNCLASSIFIED</u>